

Granville Hypalube Plus Mineral 15W/40

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Granville Hypalube Plus 15W/40 is a high quality mineral engine oil formulated with a balanced blend of quality base oil and additives to produce a lubricant that offers an excellent level of engine protection with outstanding cleanliness. Hypalube Plus 15W/40 can be used in petrol & diesel engines both turbo and naturally aspirated.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SL/CG-4
ACEA: A3/B3
MB: 229.1
Volvo: VDS-2



* Image for illustrative purposes only.

PRODUCT BENEFITS

- * Ensures lubricant performance
- * Excellent high & low temperature performance
- * Suitable for petrol and diesel engines
- * Outstanding engine cleanliness and sludge control

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Store upright and sealed sealed in a cool, dry place out of the reach of children.

SIZE	PART NO	BARCODE
1 Litre	0203	5020618002031
5 Litre	0180	5020618001805
20 Litre	0264	5020618002642
199 Litre	0126	5020618001263



Granville Hypalube Plus Mineral 15W/40

1 Litre, 5 Litre, 20 Litre & 199 Litre

SHELF LIFE

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Base Oil	: More Than 70%
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	12.5	<16.3	14.05
Viscosity, CCS -20°C	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		10.62
HTHS Viscosity	ASTM D4683	mPa.s	3.7		
NOACK Volatility	ASTM D5800	%		13	
Pour Point	ASTM D97	°C		-25	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			104.34
Density	ASTM D792	@ 15°C			0.889

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

